

Our Products

Products description

Material	Aluminium Slugs with or without holes
Alloy	AA1070
Purity	99.70% minimum
Grain Sizes	Grain 5
Hardness	16 to 19 HB
Thickness	3.00 mm. to 10.00 mm
Diameters	<p>We can supply aluminium slugs of 99.7% Al purity from our aluminium rolling mill. Slugs from Diameter 20 mm to 116 mm can be supplied. The following are the different diameters that can be readily supplied.</p> <p>20mm, 25 mm, 27mm, 40mm, 45 mm, 50 mm, 54 mm, 63.5 mm, 74 mm, 75 mm, 85 mm, 89 mm, 90 mm and, 116 mm. Slugs to customer's specifications can also be supplied.</p>
Tolerances	According to norms DIN 59604
International Standards	DIN 59604, 1721, ASTM E 112, MIL STD 105 D, EN 570
Shape	Flat, Concave, Preform
Weight	Slugs weight (grs.) is determined by the nominal dimensions of the diameters (mm), thickness (mm) and aluminum density.
Packing	Corrugated cardboard boxes (25 kg. each), on wooden pallets.

Finish

Tumble Rolled or Shot Blasted

Chemical Composition
(% maximum allowed by element)

% Si	% Fe	% Cu	% Zn	% Mg	% Mn	% Ti	% Other
0.1	0.2	0.04	0.04	0.03	0.03	0.03	0.01