

Type	Prime Aluminum Coil ,Prime Aluminum Coil
Alloy/Grade	AA1050,AA1060,AA1070,AA1100,AA3003,AA8011 ETC.
Temper/Hardness	O,H14 etc. O,H14 etc.
MOQ	3MT for each size
Technique	Cold Rolling,Cold Rolling
Thickness (mm)	0.1mm~8.0mm, 0.1mm~8.0mm
Width (mm)	20mm~2000mm,20mm~2000mm
Pallet Weight	As required,as required
Trade Terms	FOB or CIF or CNF
Delivery Time	Within 15 Days,within 15days
Inspection	SGS is acceptable
Payment	TT deposit, 100%L/C at sight and DP are acceptable
Application	Building materials,decorations,car,air conditioners,electronics etc.
Package	Standard seaworthy exporting carton, Wooden pallets,waterproof paper and plastic coverage or or as per customer's requirements
Delivery Item	FCL and LCL By 20feet container (25MT) or 40feet container (26MT)
Additional Item	Customized service is available (Size,Alloy,Temper,Packing & Pallet Weight)

Aluminum alloy guide

Alloy	Si	Fe	Cu	Mn	Mg	Zn	Cr	Ti	Other	Remain
1060	0.25	0.35	0.05	0.03	0.03	0.05		0.03	0.03	99.6
1050	0.25	0.4	0.05	0.05	0.05	0.05		0.03	0.03	99.5
1100	0.4	0.55	0.05-0.2	0.05	...	0.01			0.15	99
3003	0.6	7	0.05-0.2	1.0-1.5	...	0.01			0.15	aluminum
5052	0.25	0.4	0.1	0.1	2.2-2.8	0.1	0.15-0.35			aluminum
8011	0.25	0.5-0.9	0.6-1.16	0.1	0.2	0.01		0.08	0.15	aluminum

Dimension available of aluminum coil

Alloy	1100,1050,1060,1090,3003,3005,3105,5052
Temper	All tempers,including O.Subject to alloy
Thickness	0.1-6mm for mill finish (check for different alloys)
Width	100mm-1500mm
Length	Subject to customers option,maximum 6 meters

Packing information of aluminum coil

1)Covered by carton box

2)A wooden case beneath the coil
3)Eye to wall or eye to sky
4)With a silica Gel in the whole to anti moisture
5)Weight per coil can be subject per customer's request